



KT-KP12

Industrial Tablet with reinforced construction, designed to work under the harsh condition



Product Introduction

The KT-KP12 is a modern, water-resistant industrial tablet designed for extreme applications. It features a reinforced construction and a special design that meets IP65 requirements, ensuring protection

Product Highlights



Android12



8500mAh/3.8v



Touchscreen



IP 67



Camera 20MP

Product Specifications

Model	KT-KP12
OS Version	Android ™ 12.0
CPU Type	MTK6891(MTK 1100), 6nm, 8 core, 3*Arm Cortex-A78@2.6GHz,4*Arm Cortex-A55@2.0GHz
Memory	6GB RAM+128GB ROM
Screen	10.1" HD (1920*1200)
Touch screen	Support (Multi-point touch)
TP	Capacitive multi-touch screen G+FF
Network Connections Bands	2.4G&5GHz,dual band
Wi-Fi	Wi-Fi6, IEEE 802.11 a/b/g/n/ac/ax
Scan module 1D/2D	
Network Connections Bands	5G: N1/3/5/7/8/20/28/38/40/41/77/78/79 4G: TDD-LTE: B34/38/39/40/41; FDD-LTE:1/3/5/7/8/20/26/28A/28B;TD-SCDMA:B38/39/40/41 3G: WCDMA: B1/2/5/8; CDMA:BC0/BC1 2G: GSM:B2/3/5/8
Data Link	5G:NR 4G:TDD LTE FDD LTE 3G:HSPA+ ,EVDO , GPRS EDGE; 2G:GPRS class 12/EDGE
Camera Front	8MP FF
Camera Rear	20MP AF
Flashlight	Support
Speaker	8R, 1W*2
MIC	Support (Dual micro)
G-sensor	Support(3D)
Sensing distance	Support
Compass	Support
Motor	Support

Product Specifications

GPS	GPS/A-GPS/GLONASS/BEIDOU
Bluetooth	BT5.1
NFC	Support, 13.56MHz Contactless interface modem - ISO/IEC 18000-3 、 18092 - ISO/IEC 14443 A/B - ISO/IEC 15693 Mifare compliance
OTG	Support
TOP	Power Button*1, Volume Button*2
Left	Custom Button*2
SIM Card Slot	Dual cards(SIM+SIM or SIM+TF)
Battery Capacity	8500mAh/3.8v
Charger	DC 9V/2A
Data Cable	TYPE-C, 2.0
Dimension	254.2 x 172.6 x 13.5mm
Weight	830g
Indicator light	Support, red light charging, green light fully charged
Google GMS	Support
Working Temperature	-10°C-50°C
Storage Temperature	-20°C-70°C
Working Humidity	5%-95%
Waterproof	Ip67
Explosion proof grade	Compatible Ex ib IIC T4 Gb